




THE DATASHEET OF 122TR



THIS DOCUMENT IS THE PROPERTY OF
KEYSTONE ELECTRONICS CORP. AND
SHALL NOT BE REPRODUCED, DISTRIBUTED
OR USED AS A BASIS FOR MANUFACTURE
WITHOUT PRIOR WRITTEN PERMISSION
FROM KEYSTONE ELECTRONICS CORP.


COIN CELL TO BE
CENTERED ON
NEGATIVE CONATCT



MTG LAY OUT WHEN USE WITH P/N 118


BATTERY DIA.	L
12mm	.213 [5.4]
16mm	.291 [7.4]

COIN CELL TO BE
CENTERED ON
NEGATIVE CONATCT




MTG LAY OUT WHEN USE WITH P/N 112

BATTERY DIA.	L
20mm	.370 [9.4]
23mm	.429 [10.9]
24mm	.448 [11.4]
30mm	.567 [14.4]



CONTACT
SURFACE



ACTUAL SIZE



11.10.16 ECN 16-095, ADD EMBOSS (A1)

A

DATE

DESCRIPTION

REV.

KEYSTONE ELECTRONICS CORP.

www.keyelco.com • NEW HYDE PARK, NY 11040 • Tel (516) 328-7500

PART NAME

POSITIVE BATTERY CONTACT

MATERIAL

.006 [0.15] TH'K STAINLESS STEEL

FINISH

GOLD PLATE

DRN BY

NT

DATE

1.06.16

APP'D

RH

SCALE

5X

TOLERANCES

INCH [MM]

DECIMAL

± .005 [± 0.13]

ANGULAR

± 1°

UNLESS OTHERWISE SPECIFIED

CODE

DWG NO.

C

122