TE Internal #: 2170680-2

SFP+, Cage Assembly, Sealable, Signal, Operating Temperature


Range -55 – 105 °C [-67 – 221 °F], Data Rate (Max) 16 Gb/s, 1 Ports

View on TE.com >





Connectors > Pluggable IO Connectors & Cages











Pluggable I/O Product Type: Cage Assembly

Sealable: Yes

didio10. 100

Circuit Application: Signal

Operating Temperature Range: -55 – 105 °C [-67 – 221 °F]

Data Rate (Max): 16 Gb/s

Features

Product Type Features

Cage Type	Single
Pluggable I/O Product Type	Cage Assembly
Sealable	Yes
Form Factor	SFP+

Configuration Features

Number of Ports	1
Port Matrix Configuration	1 x 1

Electrical Characteristics

Termination Features

Housing Features

Dimensions



PCB Thickness (Recommended)	1.5 mm
Usage Conditions	
Operating Temperature Range	-55 – 105 °C[-67 – 221 °F]
Operation/Application	
Pluggable I/O Applications	SFP+
Heat Sink Compatible	Yes
Circuit Application	Signal
Packaging Features	
Packaging Method	Tray
Other	
Included Lightpipe	No
EMI Containment Feature Type	Internal/External EMI Springs

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach



Compatible Parts



TE Part # CAT-C11-N490333

QSFP28-Four SFP+ Cable Assembly:
30 AWG



TE Part # CAT-C11-N490325

QSFP28-Four SFP+ Cable Assembly:
26 AWG



TE Part # 2334985-2 SFP28 DIRECT ATTACH CA, 1M, 32AWG



AWG



TE Part # CAT-C11-N49011 SFP28 to SFP28 Cable Assembly: 26 AWG



TE Part # CAT-Q17-N49011 QSFP56-Four SFP56 Cable Assembly: 30 AWG



TE Part # CAT-Q17-N490333 QSFP56-Four SFP56 Cable Assembly: 26 AWG



TE Part # 4-2821224-5 SFP56 DIRECT ATTACH CA, 3M, 26AWG



TE Part # 4-2334985-2 SFP56 DIRECT ATTACH CA, 1M, 32AWG



TE Part # 4-2821222-5
SFP56 DIRECT ATTACH CA, 2M,
30AWG



TE Part # 2821033-8 QSFP TO [4]SFP+, 28G, 1M, 33AWG

Customers Also Bought

















TE Part #CQ50303001 RAY-101-10.0(10)



TE Part #224512-E MSPEED 50 F SMD F6 * AB VV 137 094 * * E



TE Part #0730466001 DR-25-3/16-0-FAR-10M

Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2170680-2_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2170680-2_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2170680-2_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Application Specification

English