




# THE DATASHEET OF 1043

# "18650" LITHIUM-ION BATTERY HOLDERS

### SMT Polarized



1048P (Dual Cell)  
Not Shown

## APPLICATIONS

- Accommodates cells with or without built-in PCB protection circuits
- Polarity clearly marked for orientation
- Polarized holders available for protection against improper battery installation


**Operating Temp Range:**  
-60°F to +290°F (-50°C to +145°C)

- Computer memory, power backup systems
- Digital readers
- Laptop and touch pad computers
- PLC and industrial controls
- Electronic cigarette/vapor industry



PC Battery Clip  
Available  
See Page 11.

## SURFACE MOUNT



## SPECIFICATIONS

**Base:** High Temp Nylon 46, UL 94V-0  
**Contacts:** .012 (.30) Stainless Steel,  
Gold Plate (Flash)


**CAT. NO. 1042** Leaf Springs**CAT. NO. 1042P** Polarized Holder

**Packaging Spec's:** 50 pieces per tray

**Packaging Spec's:** 50 pieces per tray

**Packaging Spec's:** 50 pieces per tray

## DUAL CELL



## SPECIFICATIONS

**Base:** High Temp Nylon 46, UL 94V-0  
**Contacts:** .012 (.30) Stainless Steel,  
Gold Plate (Flash)

**CAT. NO. 1048** Dual Springs

**CAT. NO. 1048P** Polarized Holder**Packaging Spec's:** 25 pieces per tray

**Packaging Spec's:** 25 pieces per tray

**Packaging Spec's:** 25 pieces per tray